

EV Protec FZ

G18, phase 3, Dubai industrial
City, Dubai, UAE
T. +971 44209669 | +971 551393968
Email.info@evprotec.com



DATASHEET

EV PROTEC

60KW DC CHARGER DUAL GB/T

DCCHA-60KWC-2411



APPLICATION Home | commercial | Apartments

SPECIFICATION TABLE

ITEM	DESCRIPTION
INPUT	Input Voltage AC400V±10%,3P+N+PE
	Working frequency 45-65HZ
	The power factor ≥0.99
	Input current 0-125A
	Input cable length Non
OUTPUT	Power 60KW
	Voltage DC 200-1000V
	Output Current CCS2:MAX200/250A , GBT:MAX 200/250A
	Connector Type GBT
	Gun Line Length Car: 4.5m , Bus: 6.5m(optional)
	Charger plug Single plug/ Dual plugs
	Efficiency ≥95%
WORKING CONDITIONS	Temperature range -40~55℃
	Humidity range 5~95RH%: (non-condensation)
	The altitude 2000M
	Location Indoor/outdoor
MECHANICAL SPECIFICATION	User Interface LED+7"LCD Screen
	Communication Interface Ethernet/4G(Optional)/WIFI(Optional)
	Packing/weight About 185KG
	IP IP55
START MODE	App/RFID(Optional)

PROTECTION FUNCTION	Scram ; Input over/under voltage ; Output overvoltage ; Overtemperature ; Overcurrent ; Short circuit ; Leakage ; Lightning ; Battery reverse; Insulation monitoring ;
LANGUAGE	Default English, other languages can be customized
INSTALLATION	Wall-mounted/ Stand- mounted Cable requirement 3x35mm 3p and 2x16mm (N&E)
CHARGER STANDARD	GB/T
MANUFACTURED BY	NIZINE LLC - USA UK UAE SG HK
BRAND	EV PROTEC - UK