

GIBIZ

CCS2 to GBT Connector

MODEL: FWL-VWGIBIZ-IP55



PRODUCT INFORMATION

The product is only applicable to the COMBO2 charger station for the GB/T Vehicle DCfast charging

APPLICATION Vehicles | Automobile

SPECIFICATION TABLE

SPECIFICATION	VALUE	UNIT
Amperes	200	A
Input	150 - 900	VDC
IIP Rating	55	IP
Operating Temperature	-22°F to 122°F - 30 °C to +50 °C	°C
Storage Temperature	-40°F to +185°F -40 °C to +85°C	°C
Packing size	(L* W* H) 35 0 * 1 7 2 * 1 1 5	mm
Weight	2	kg
BRAND	EV PROTEC	

PRODUCT IMAGERS



PLUGGING IN CAUTION:

Please pay attention to check whether there is any damage or incomplete structure before using the device.

- 1 To open your DC charge port on your GB/T vehicle, Turn off the dashboard and place on "P" gear.
- 2 Attach the adapter inlet to the end of the charging station's charge cable by lining up the COMBO 2 with the charge cable and pushing until it snaps into place.
- 3 Plug the GB/T plug into your GB/T vehicle, and operate COMBO 2 charging station when indicating 'plug in', then plug in Combo 2 plugin COMBO 2 port.
- 4 Follow the instructions on the COMBO2 charging station to start the charging session.



UNPLUGGING When charging is complete:

- 1 Press the unlock hatch bottom of the adapter, pull the adapter out of the GB/ T DC charge port, CAUTION: If you unplug the charging station's cable from the adapter when the adapter is still plugged into the vehicle, make sure the adapter does not fall onto the vehicle and cause damage.
- 2 Push the charge port door closed.
- 3 Unplug the adapter from the charging station and store it in an appropriate location